RAPIDGUARD[®] II



SYSTEM COMPLIANCE

ANSI | ISO | OSHA | RIA Standards

RapidGuard® II

• Unique Lift-Off design allows for the removal of guards (panels) while the fixing system (hardware) remains attached to the guards (post), in compliance with RIA TR R15.406.

- 50% faster install than most competing products.
- Can be installed by 1 person due to the Patent Pending T-Slot mounting solution.

Safe Distance from a Hazard

| Mesh Opening | Safe Distance |
|------------------------------------|---------------------------|
| 1 ¼" Center to Center | 4.7″ (120mm) |
| 2" Center to Center | 33.46" (850mm) |
| System Heights | Panel Widths |
| <mark>6' - 6</mark> ¾" (2000.25mm) | 1' to 5' in 1' increments |
| 8'-5 ¼" (2571.75mm) | |

Sweep Space

5 1/4" (133.35mm) complies with all existing OSHA/ANSI/RIA/ISO standards.



WIRECRAFTERS.COM | (800) 252-2636 | (502) 363-6691 | 6208 STRAWBERRY LANE | LOUISVILLE, KY 40214-2929

RapidGuard® II

- Panels install vertically between 6' 6 ¾"H & 8' 5 ¼"H Posts (5 ¼" sweep).
- Fully framed panel adds strength and stability.

• Unique Lift-Off design allows for the removal of guards (panels) while the fixing system (hardware) remains attached to the guards (post), in compliance with RIA TR R15.406.

- 5/16"-18 x 3/4" tool removable hardware is compliant with ANSI B11.19 and RIA TR R15.406.
- All hardware including anchors included.
- Stock powder coated black panels & yellow posts.
- Panels contain 1 1/4" SQ (center to center) 10GA Welded Wire
- An integrated lock out plate and pull handle are standard on hinge doors.
- Safety Interlocks available with mounting plates.
- 13 GA 1 ¼" x 1 ¼" roll formed angle.
- 2" SQ 14GA posts with 6" SQ x ¼" baseplates
- Standard size panel heights are 6' 1 1/2"H & 8'H by 1' to 5'W

